

CIVIA

MARKET FRONT BASKET & PIZZERIA RACK INSTALLATION

WARNING: Read these instructions completely before beginning installation of this product. If you lack the knowledge or tools to perform this installation, please have your local professional bicycle mechanic do the job. Improper installation can result in loss of control, damage to the bicycle, and/or serious injury or death to the rider.

Required tools: 4 and 5mm hex wrenches
8, 10 and 13mm box-end wrenches
Hacksaw and guide

STEP 1

- Turn rack over and assemble as shown in (Figure 1). Snug all bolts, but don't tighten fully. NOTE: Lightmount is optional

STEP 2

- Turn rack right side up
- Install M5 bolts with 4mm hex wrench through barrel sleeves and attach to tombstone mounts to rack (Figure 2)

STEP 3

- Install M6 x 40mm bolt and assembly through fork crown. Again, snug the bolts, but don't tighten fully

STEP 4

- Attach struts to fork dropout or midblade

STEP 5:

Finish installation

- Make sure the rack is level from front to back, and side to side
- Depending on the bike's size, this may require you to shorten the stays by cutting them. To do so, remove them from rack, then cut using a hacksaw and cutting guide. File any rough edges (Figure 3)
- Fully tighten down all the rack bolts to 2.3–2.9Nm recommended torque
- Load up your bike and go for a ride

WARNING: The Market Basket and the Pizzeria Rack are designed to carry up to 22 lb (10kg). Do not exceed the load capacity. The Market Basket and the Pizzeria Rack are not designed to carry pets or passengers. Always properly secure your cargo before riding.

A copy of these instructions can be found at civiacycles.com/safety.



Parts and required tools



Figure 1



Figure 2



Figure 3



Market Front Basket



Pizzeria Rack

